

## ONVIF 2 Megapixel K10 Level Vandal Dome IP Camera




IP Surveillance

### iMPIRVFD-2SN

- Sony Exmor 1/2.8" CMOS Image Sensor.
- Real-time Dual Codec
- Resolution: 1920x1080.
- Simultaneous Multiple Streams.
- 24 IR LEDs, IR Range 15M ~49 FT
- Supports ONVIF Standard to Simplify Integration and Enhance Interoperability.





# iMPiRVFD-2SN

2 Megapixel K10 Level Vandal Dome IP Camera



## Full function cable



1. GND
2. Alarm output 1
3. Alarm input 2
4. Alarm input 1
5. DC12V input
6. Reset Button
7. Analog Video Out
8. Audio Line in
9. RJ-45 Ethernet LAN Port

## SPECIFICATIONS

System	Flash	: 16MB
	RAM	: 128MB
Image Sensor	FullHD High Quality 1/2.8" Sony Exmor CMOS Image Sensor	
Sensitivity	0 Lux (IR ON)	
IR LEDs	24PCS	
IR Range	15M	
Lens	Varifocal 2.8-12mm F1.4	
	Removable IR-cut filter for day & night function	
Video	H.264: 1920x1080 @25fps	
	H.264: 1280x720 @30fps	
	H.264: 640x480 @30fps	
	Compression: H.264, MJPEG Streaming: Dual Codec (H.264 · JPEG) Selectable Support Simultaneous multiple streams	
Image Settings	Adjustable image size, quality, and bit rate	
	Time/Date stamp and text caption overlay.	
	BNC connector for video output, NTSC/PAL video output switch	
	Adjustable image size, quality, and bit rate	
	Time/Date stamp and text caption overlay.	
	Configurable brightness, contrast, saturation, sharpness, white balance and exposure AGC / AWB / AES / BLC / WDR	
Networking	Interface	10/100 Mbps Ethernet, RJ-45
	Supported Protocol	IPv4, TCP/IP, DHCP, HTTP, RTSP, SNTP, DNS
	Supported Browser	Microsoft Internet Explorer 6.0 or above Safari, Chrome or Firefox
Alarm and Event	Motion Detection	
Managemment	Event notification using SMTP or FTP	
Users	8 clients on-line monitoring at the same time	
	Multi-level user access control with password protection	
Maintenance	Supports online firmware upgrade	
I/O port	RJ-45 Ethernet x 1, DC Jack x 1, BNC Video out, Phone Jack Line in x 1,	
	Alarm I/O, Reset Botton	
IP Rating	IP66	
Power	DC12V or PoE IEEE802.3af Class 0	
Max. Power Consumption	3.6W(IR OFF), 7W(IR ON)	
Weight	Netweight: 1050g	
Dimension	W:Φ135mm H:110mm	
Operating Environments	Temperature: 0 ~ 45 °C , Humidity: 90%	

★ Product specifications are subject to change without notice; please contact us for the latest information.

