

# 5MP/3MP/2MP/1080P/720P Vandal Dome

ONVIF



## Features:

- High quality 1/2.5" CMOS Sensor.
- Real-time H.264, MPEG-4 and MJPEG Compression(Triple Codec).
- Resolution : 5 Mega Pixel 2592x1920.
- Simultaneous Multiple Streams.
- 30 IR LEDs.
- Supports ONVIF, 2.X, RTSP Standard to Simplify Integration and Enhance Interoperability.
- Built-in MicroSD/SDHC Card Slot for On-board Storage.
- Supports ONVIF Standard to Simplify Integration and Enhance Interoperability.
- Support Audio line-in for external microphone.
- Vandal-Resistant Case Design.



System	CPU : TI TMS320DM368 Flash : 256MB RAM : 128MB	
Image Sensor	High Quality 1/2.5"CMOS	
Lens	Varifocal 3.5-10mm F1.6 Removable IR-cut filter for day & night function	
Sensitivity	0 Lux(IR ON)	
IR LED	30PCS LEDs	
Video	H.264: 30 fps at 1920x1080 , Highest Resolution: 10 fps at 2592x1920 MPEG4: 30 fps at 1920x1080 MJPEG: 30 fps at 1920x1080 , Highest Resolution: 10 fps at 2592x1920 Compression: H.264, MPEG-4 & MJPEG Streaming: Triple Codec (H.264 ∙ MPEG-4 ∙ JPEG) Selectable Support Simultaneous multiple streams BNC connector for video output ; NTSC/PAL video output switch Adjustable image size, quality, and bit rate	
Image Settings	Time/Date stamp and text caption overlay. Configurable brightness, contrast, saturation, sharpness, white balance and exposure AGC ∙ AWB ∙ AES ∙ BLC	
Audio	Format	MPEG-4 AAC audio encoding G.711 audio encoding
	Support Audio line-in for external microphone	
Networking	Interface	10/100 Mbps Ethernet, RJ-45
	Supported Protocol	IPv4,TCP/IP,DHCP,HTTP,RTSP,SNTP,DNS
	Supported Browser	Microsoft Internet Explorer 6.0 or above QuickTime Player is necessary add-in for Safari, Chrome or Firefox
Alarm and Event Management	Motion Detection Event notification using SMTP or FTP through CMS FCW-SE064 Smart Motion Detection Triggered Nighttime color image	
Users	8 clients on-line monitoring at the same time Multi-level user access control with password protection	
On-board Storage	Micro SD/SDHC card slot : Stores snapshots and video clips	
Maintenance	Supports online firmware upgrade	
I/O	RJ-45 Ethernet x 1,DC Jack x 1,BNC Video out, Phone Jack Line in x 1,MicroSD Slot*1	
Power	DC12V or PoE IEEE802.3af Class 0	
Weight	Netweight : 1050g	
Dimension	W:Φ150mm H:110mm	
Operating Environments	Temperature: 0 ~ 45 °C Humidity: 90%	