

30x Outdoor PTZ Dome

480 TVL Day/Night



Image Sensor	1/4" SONY Interline Transfer CCD
Effective Pixels	NTSC: 768(H)× 494(V)
Sensing Area	3.6mm× 2.4mm
Signal System	PAL/NTSC
Horizontal Resolution	480 TV Line
Built-in Lens	30X, 3.9-85.8mm
Minimum Illumination	0.05Lux (With external IR LED on 0 Lux)
Sync. System	Internal
Shutter Speed	1/50(1/60)--1/100, 000(s)
S/N Ratio	More than 52dB
OSD	English
White Balance	Auto
Auto color to B/W	Auto color to W/B
Focusing System	Digital focus
Control Interface	Line Control
Communication Port	R485
Video Output	1.0Vp-p, 75Ω (BNC)
Internal Camera	DC12V/750mA
Video Out	VIDEO OUT (BNC)
VIDEO OUT (BNC)	102× 57× 67 (mm)
Input voltage	AC24V 50&-60HZ
Input Power	Pan/tilt 10VA
Heater power	AC24V 22W
Heat Action Range	NO. 10* C +/- 5 OFF: 26* C +/- 5
Angle available	Pan: 0* - 350* tilt 0*-90*
Moving velocity	Pan 12* /s tilt 12* /s
Limitation	Pan/tilt adjustable
Max size of lens Adding camera	7" 135x65x66mm 9" 170x75x70mm 12" 238x80x75mm
Structure	Housing: DMC Pan/tilt: aluminum Optical cover: Aerylic